

# Holdwell

## (Hengwei Weiye Electronic)

恒威伟业电子材料有限公司

Silver alloy wire - (Ag≥88.1%, Pd≤3.5%, Au≤8.4%)

Products model	Material composite	Wire size	Breaking load (gm)	Elongation (%)	Application
S01-18	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	18um/0.7mil	4-8	5-15	LED & IC Assembly
S01-20	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	20um/0.8mil	6-10	5-15	LED & IC Assembly
S01-23	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	23um/0.9mil	8-12	5-15	LED & IC Assembly
S01-25	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	25um/1mil	9-13	5-15	LED & IC Assembly
S01-30	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	30um/1.2mil	13-17	5-15	LED & IC Assembly
S01-38	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	38um/1.5mil	23-27	5-15	LED & IC Assembly
S01-50	Ag≥88.1%,Pd≤3.5%,Au≤8.4%	50um/2mil	46-50	5-15	LED & IC Assembly

Silver alloy wire - (Ag>96%,Pd<4%)

Products model	Material composite	Wire size	Breaking load(gm)	Elongation (%)	Application
S11-18	Ag>96%, Pd<4%	18um/0.7mil	3-11	9-16	IC Assembly
S11-20	Ag>96%, Pd<4%	20um/0.8mil	4-11	9-16	IC Assembly
S11-23	Ag>96%, Pd<4%	23um/0.9mil	6-13	9-16	IC Assembly
S11-25	Ag>96%, Pd<4%	25um/1mil	8-17	9-16	IC Assembly
S11-28	Ag>96%, Pd<4%	28um/1.1mil	9-20	9-16	IC Assembly
S11-30	Ag>96%, Pd<4%	30um/1.2mil	10-22	9-16	IC Assembly

Other wire size or specification available upon request



Axend Pte Ltd  
 100D Pasir Panjang Rd #04-01 Meissa  
 Singapore 118520  
 Tel : +65 6748 7011 Fax : +65 6748 7012  
 Website: [www.axend.biz](http://www.axend.biz)  
 Youtube: Axend's Youtube Channel